



# HANKISON

[hankisonintl.com](http://hankisonintl.com)



**HF SERIES**

**COMPRESSED**

**AIR FILTERS**

**SPX Air Treatment**

# Compressed Air Treatment Reduces Operating Costs

**Cut the Cost of Compressed Air. Hankison filters remove more contaminants with less pressure drop. Compare the operating pressure drop of competitive brands and remember that for every extra 2 psi of pressure drop, power input needs to be increased by 1%.**

## From the Leader in Compressed Air Treatment

Since Hankison first developed their coalescing filters in the 1970s, they have been a leader in filtration design. HF Series filters are the result of extensive testing of the latest state-of-the-art materials, in filtration media. Filter elements have been designed utilizing the latest media innovations and manufacturing techniques. The result is increased performance, reduced size and lower operating pressure drop, in a variety of grades to match your requirements. Housings have large flow areas to reduce pressure drop and to allow easier installation, operation, and maintenance. A systems approach has been used to allow for convenient matching of filter types to achieve the air quality you desire, while comprehensive third party testing guarantees performance to CAGI, ISO, and PNEUROP\* standards.

With a greater selection of filter grades, more models to choose from, and worldwide technical and service support, Hankison offers a systemized solution for your compressed air quality needs.

## Let Hankison Give You the Compressed Air Quality You Require

A typical compressed air system is contaminated with...abrasive solid particles such as dust, dirt, rust and scale...compressor lubricants (mineral or synthetic)...condensed water droplets and acidic condensates...and oil and hydrocarbon vapors.

If not removed, these contaminants increase pneumatic equipment maintenance costs, lead to instrument and control failure, contribute to poor product fit and finish and contaminate processes.

The right Hankison filter or filter system will remove these contaminants allowing your compressed air system to deliver the quality of air required by your application... whether it's plant air, instrument air, or medical air...helping to ensure consistent output quality while minimizing operating costs.

## ISO 8573.1 Quality Classes

Class	Solid Particles			Humidity and Liquid Water		Oil	
	Particle Size, d (micron)			Pressure Dew Point		Total concentration, Aerosol, Liquid, and Vapor	
	0.10 < d ≤ 0.5	0.5 < d ≤ 1.0	1.0 < d ≤ 5.0	°C	°F	mg / m <sup>3</sup>	ppm w/w
	Maximum Number of Particles per m <sup>3</sup>			°C		mg / m <sup>3</sup>	
0	As Specified			As Specified		As Specified	
1	100	1	0	≤ -70	≤ -94	≤ 0.01	≤ 0.008
2	100,000	1,000	10	≤ -40	≤ -40	≤ 0.1	≤ 0.08
3	Not Specified	10,000	500	≤ -20	≤ -4	≤ 1	≤ 0.8
4	Not Specified	Not Specified	1,000	≤ +3	≤ +38	≤ 5	≤ 4
5	Not Specified	Not Specified	20,000	≤ +7	≤ +45		
6				≤ +10	≤ +50		
				Liquid Water Content, C <sub>w</sub> g/m <sup>3</sup>			
7				C <sub>w</sub> ≤ 0.5			
8				0.5 < C <sub>w</sub> ≤ 5			
9				5 < C <sub>w</sub> ≤ 10			

Per ISO8573-1: 2001(E)

## Modular Housings for Flows through 780 scfm

- Enlarged flow paths reduce pressure drop
- Manufactured from top quality aluminum, zinc, and steel
- Chromated and epoxy powder painted (interior and exterior) for added durability and corrosion resistance
- 300 psig (21 kgf/cm<sup>2</sup>) maximum working pressure (tested to a 5:1 safety factor)

## Easy to Install

- Modular connections - allow housings to be connected in series easily, while saving space
- Wall mounting bracket optional
- Can be mounted for left or right entry
- New space saving design reduces service clearances



## Easy to Maintain

- 1/8 turn, self locking bayonet head to bowl connections (through 1")
- Push on elements make element replacement quick and easy
- If housing is not depressurized before disassembly, escaping air gives audible warning
- Captive o-ring
- Ribbed bowls allow use of C spanner
- Color coded elements for easy identification

## Easy to Operate

### New differential pressure indicators

Indicates optimum time for element change-maximizing your element investment while minimizing pressure drop

### Slide indicator

Economical-changes color when filter element requires replacement

### Gauge

- Large easy to read gauge face
- Dual gauge faces allow housings to be mounted in any flow direction
- Can be mounted remotely
- Switch for remote indication available

### Liquid level indicator

- Allows visual monitoring of liquid level and signals the need for preventative maintenance to avoid downstream contamination
- Manufactured from thermoset polyurethane, compatible with synthetic lubricants

### Internal automatic drains

- Pilot operated, pneumatically actuated... reliably discharges collected liquids
- Viton seals...totally compatible with synthetic lubricants
- Inlet screen for additional protection
- Discharge fitting threaded to facilitate drain line connection




# Hankison Elements Offer Enhanced Performance and Low Pressure Drop

## A choice of Seven element Grades allows you to design a system that delivers the air quality you require

- Push-on elements make element replacement easy
- Piston type element to housing seal keeps unfiltered air from by-passing element
- Corrosion resistant cores
  - Stainless steel for added structural integrity
  - Low resistance to flow
  - Seam welded for extra strength
- New "matrix blended fiber" media
  - Large, effective surface area - improves capture rate - ensures high efficiencies
  - Large open area minimizes pressure drop
- Coated, closed cell foam sleeve
  - Resists chemical attack from oils and acids
  - Ensures high efficiencies by preventing re-entrainment of coalesced liquids
- Chemically resistant end caps bound to media with specially formulated adhesive
- Silicone free
- Withstands temperatures to 150°F (66°C)

### Grade 11 ■




#### Moisture Separator

bulk liquid removal. Maximum inlet liquid Load: 30,000 ppm w/w

#### Filtration

- Two stainless steel orifice tubes provide 10 micron mechanical separation

### Grade 7 ■



#### General Purpose Air Line Filter


for removal of liquid water and oil; removes solid particles to 1 micron (1.0 ppm w/w maximum remaining oil content) <sup>1</sup>

- Corrosion resistant inner and outer cores

#### Two-stage filtration

- **First stage** - captures larger particles with alternate layers of fiber media and media screen
- **Second stage** - coalesces aerosols and captures solid particles with multiple layers of epoxy bonded, blended fiber media

### Grade 9 ■




#### Separator/Filter

mechanical for bulk liquid removal plus a 3 micron coalescer (5 ppm w/w maximum remaining oil content) <sup>1</sup>

#### Two-stage filtration

- **First stage** - two stainless steel orifice tubes provide 10 micron mechanical separation
- **Second stage** - in-depth fiber media captures solid and liquid particles to 3 microns

### Grade 6 ■



#### Dry Particulate Air Line Filter

for removal of solid particles to 1 micron


#### Two-stage filtration

- **First stage** - coalesces aerosols and captures solid particles with multiple layers of epoxy bonded, blended fiber media
- **Second stage** - captures larger particles with alternate layers of fiber media and media screen

<sup>1</sup> Filter efficiencies have been established in accordance with CAGI standard ADF400 and are based on 100°F (38°C) inlet temperature.

<sup>2</sup> Filter efficiency has been established in accordance with CAGI standard ADF500 and is based on 100°F (38°C) inlet temperature.

## Grade 5 ■



### High Efficiency Oil Removal Filter


for coalescing fine water and oil aerosols; removes solid particles to 0.01 micron (0.008 ppm w/w maximum remaining oil content)<sup>1</sup>

- Corrosion resistant inner and outer cores

### Two-stage filtration

- **First stage** - multiple layers of fiber media and media screen remove larger particles, prefiltering the air for the second stage
- **Second stage** - multiple layers of bonded, blended fiber media for fine coalescence
- Outer coated, closed cell foam sleeve

## Grade 3 ■



### Ultra High Efficiency Oil Removal Filter

for coalescing ultra-fine oil aerosols; removes solid particles to 0.01 micron (0.0008 ppm w/w maximum remaining oil content)<sup>1</sup>

- Corrosion resistant inner and outer cores

### Two-stage filtration

- **First stage** - coated, closed cell foam sleeve acts as prefilter and flow disperser
- **Second stage** - multiple layers of matrix blended fiber media for ultra-fine coalescence
- Outer coated, closed cell foam sleeve

## Grade 1 ■



### Oil Vapor Removal Filter

for removal of oil and hydrocarbon vapors normally adsorbable by activated carbon; removes solid particles to 0.01 micron (0.003 ppm w/w maximum remaining oil content)<sup>2</sup>

- Corrosion resistant inner and outer cores

### Two-stage filtration
















- First stage - a stabilized bed of finely divided carbon particles removes the majority of the oil vapor
- Second stage - multiple layers of fiber media with bonded microfine carbon particles remove the remaining oil vapor
- Multiple layers of fine media prevent particle migration
- Outer coated, closed cell foam sleeve prevents fiber migration
- Designed for 1000 hour life at rated conditions

## Air Quality/Pressure Drop

Grade	Solid Particles Down to micron	Remaining Oil Content ppm by weight	Pressure Drop at Rated Conditions psid [kgf/cm <sup>2</sup> ]	
			Dry	Wet
11 ■	10	-	0.8 [0.06]	0.8 [0.06]
9 ■	3	5	1 [0.07]	1.5 [0.11]
7 ■	1	1	1 [0.07]	2 [0.14]
6 ■	1	-	1 [0.07]	-
5 ■	0.01	0.008	1 [0.07]	3 [0.21]
3 ■	0.01	0.0008	2 [0.07]	6 [0.42]
1 ■	0.01	0.003	1 [0.07]	NA

# Application Guide, Product Features and Specifications

## Application Guide

Element Type	Description	CAGI, PNEUROP, and ISO Performance Data	Where Used
<b>Grade 11</b>  Water Separator Element	Bulk Liquid Separator • Bulk Liquid	<u>Removes:</u> • Liquids and Solids 10 microns and larger  Maximum inlet liquid load: 30,000 ppm w/w	Downstream of aftercoolers 
<b>Grade 9</b>  Separator / Element	Mechanical separator and 3 micron coalescer removes • Liquid • Large particles	<u>Removes:</u> • Solids and liquids 3 microns and larger • Remaining oil content 5 ppm w/w  ISO 8573.1 Quality Class - Solids: Class 3, Oil Content: Class 5 Maximum inlet liquid load: 25,000 ppm w/w	At point-of-use if no aftercooler/separator used upstream 
<b>Grade 7</b>  Air Line Element	General Purpose 1 micron coalescer for shop air operating • Tools • Motors • Cylinders	<u>Removes:</u> • Solids and liquids 1 micron and larger • Remaining oil content 1 ppm w/w  ISO 8573.1 Quality Class - Solids: Class 2, Oil Content: Class 4 Maximum inlet liquid load: 2,000 ppm w/w	Upstream of ultra high efficiency oil removal filters At point-of-use if aftercooler/separator installed upstream 
<b>Grade 6</b>  Dry Particulate Element	Dry Solids Removal • Pipeline Protection from abrasive desiccant dust	<u>Removes:</u> • Solids 1 microns and larger  No liquid should be present at filter inlet	Downstream of pressure-swing (heatless) desiccant dryers 
<b>Grade 5</b>  High Efficiency Oil Removal Element	Fine coalescer for oil free air for industrial use • Painting • Injection molding • Instruments • Control valves	<u>Removes:</u> • Solids and liquids 0.01 micron and larger • 99.99+% of oil aerosols; remaining oil content 0.008 ppm w/w  ISO 8573.1 Quality Class - Solids: Class 1, Oil Content: Class 2 Maximum inlet liquid load: 1,000 ppm w/w	<u>Removes:</u> • Solids and liquids 0.008 micron and larger 99.99+% of oil aerosols; remaining oil content 0.01 ppm w/w  ISO 8573.1 Quality Class - Solids: Class 1, Oil Content: Class 2 Maximum inlet liquid load: 1,000 ppm w/w 
<b>Grade 3</b>  Ultra High Efficiency Oil Removal Element	Ultra fine coalescer for oil free air for critical applications • Where air contacts product • Conveying • Agitating • Electronics manufacturing • Nitrogen replacement	<u>Removes:</u> • Solids and liquids 0.01 micron and larger 99.999+% of oil aerosols; remaining oil content 0.0008 ppm w/w  ISO 8573.1 Quality Class - Solids: Class 1, Oil Content: Class 1 Maximum inlet liquid load: 100 ppm w/w	Upstream of desiccant or membrane dryers; use a Grade 7 as a prefilter if heavy liquid loads are present Downstream of refrigerated dryers 
<b>Grade 1</b>  Oil Vapor Removal Element	Activated carbon filter for odor free air for • Food and drug manufacturing • Breathing air • Gas processing	<u>Removes:</u> • Oil vapor: remaining oil content 0.003 ppm w/w (as a vapor) • Solids 0.01 micron and larger  ISO 8573.1 Quality Class - Solids: Class 1, Oil Content: Class 1  No liquid should be present at filter inlet - use a high efficiency oil removal filter upstream of Grade 1 filters to prevent liquid oil contamination	Downstream of high efficiency oil removal filters 
Filter Type	Description	CAGI, PNEUROP, and ISO Performance Data	Where Used
<b>HTA Series</b>  High Temperature Dry Particulate	High Temperature Dry Particulate After Filter	<u>Removes:</u> • Solids 1 micron and larger  No liquid should be present at filter inlet	Downstream of heat reactivated desiccant dryers 

## Sizing

To find the maximum flow at pressures other than 100 psig (7 kgf/cm<sup>2</sup>), multiply the Max. Flow (from tables below) by the Correction Factor corresponding to the minimum pressure at the inlet of the filter. Do not select filters by pipe size; use flow rate and operating pressure.

Minimum Inlet Pressure	psig	20	30	40	60	80	100	120	150	200	250	300
	kgf/cm <sup>2</sup>	1.4	2.1	2.8	4.2	5.6	7.0	8.4	10.6	14.1	17.6	21.1
Correction Factor		0.30	0.39	0.48	0.65	0.82	1.00	1.17	1.43	1.87	2.31	2.74

## HTA Series Product Specifications

Model Number	Max. Flow @ 100 psig scfm	MWP <sup>1</sup> @ 450°F psig	Connections <sup>2</sup>	Dimensions				Weight	
				W	H	in.	mm	lbs.	kg
HTA100	100	250	1" NPT	4.25	108	14.31	364	13	5.9
HTA200	200	250	1" NPT	4.25	108	23.81	605	19	8.6
HTA400	400	165	3" NPT	10.25	260	39.56	1005	95	43
HTA600	600	165	3" NPT	10.25	260	39.56	1005	95	43
HTA1200	1,200	165	3" NPT	16.00	406	41.44	1053	159	72
HTA1800	1,800	165	3" NPT	16.25	413	43.25	1099	219	99
HTA2400	2,400	165	4" ANSI Flange	20.00	508	54.69	1389	236	107
HTA3000	3,000	165	4" ANSI Flange	20.00	508	54.69	1389	239	108
HTA4800	4,800	165	6" ANSI Flange	24.00	610	53.00	1346	319	145
HTA6600	6,600	165	6" ANSI Flange	28.00	711	62.00	1575	548	249
HTA8400	8,400	165	6" ANSI Flange	28.00	711	62.00	1575	548	249
HTA11400	11,400	165	8" ANSI Flange	33.00	838	68.19	1732	772	350

Pressure drop: At rated flow conditions pressure drop will be less than 1 psid (0.07 kgf/cm<sup>2</sup>). Pressure drop will increase only as the filter cartridges become loaded with solid particles.

Filter cartridge replacement: Filter cartridges should be replaced annually or, when pressure drop across the cartridge exceeds acceptable differential pressure. Maximum temperature: 450°F (232°C)

<sup>1</sup> Units with higher MWP are available; contact factory. Model HTA1200 and larger are ASME code constructed and stamped.

<sup>2</sup> BSP connections and DIN Flanges are available.

## HF Series Product Specifications

Model Number	Max. Flow @ 100 psig scfm	Connections NPT / ANSI Flg.	Standard Features					Max. Pressure & Temp.		Dimensions				Weight		Replacement Element			
			11	9	7, 5, 3	6	1	Manual Drain	With D	H in	mm	W in	mm	lb	kg	Model	Qty.		
Modular Type Housings																			
HF(Grade)-12-(Conn.)-(Features)	20	3 - 3/8" NPTF or 4 - 1/2" NPTF	D	D	D	P	N/A (2)	300 psig 21kgf/cm <sup>2</sup>	250 psig 17.6 kgf/cm <sup>2</sup>	8.15	207	4.13	105	4.2	1.9	E (Grade)-12	1		
HF(Grade)-16-(Conn.)-(Features)	35		P	P	P					E (Grade)-16									
HF(Grade)-20-(Conn.)-(Features)	60		L	L	L					E (Grade)-20									
HF(Grade)-24-(Conn.)-(Features)	100	6 - 3/4" NPTF or 8 - 1" NPTF	D	D	D	G				15.32	389	5.25	133	6.3	2.9	E (Grade)-24			
HF(Grade)-28-(Conn.)-(Features)	170		G, L	G						L	E (Grade)-28								
HF(Grade)-32-(Conn.)-(Features)	250		(1)	L						L	E (Grade)-32								
HF(Grade)-36-(Conn.)-(Features)	375	8 - 1" NPTF or 10 - 1-1/4" NPTF or 12 - 1-1/2" NPTF	(1)	L	L	G				150°F 66°C	150°F 66°C	27.29	693	6.44	164	11.3		5.1	E (Grade)-36
HF(Grade)-40-(Conn.)-(Features)	485	16 - 2" NPTF or 20 - 2-1/2" NPTF	(1)	G (1)	D G					31.08	789	7.63	194	28	12.7	E (Grade)-40			
HF(Grade)-44-(Conn.)-(Features)	625	20 - 1/2" NPTF								36.83	935	7.63	194	33	15.0	E (Grade)-44			
HF(Grade)-48-(Conn.)-(Features)	780	42.96				1091				7.63	194	38	17.2	E (Grade)-48					
ASME Pressure Vessels																			
HF(Grade)-52-(Conn.)-(Features)	625	24 - 3" NPTM 80 - DN 80 Flange	(1)	G (1)	G (1)	G	N/A (1)	300 psig	300 psig	40.88	1038	10.25	260	36	16.3	E (Grade)-PV	1		
HF(Grade)-54-(Conn.)-(Features)	1,000									48.00	1219	16.00	406	91	41.3	E (Grade)-54	2		
HF(Grade)-56-(Conn.)-(Features)	1,250									48.00	1219	16.00	406	91	41.3	E (Grade)-PV			
HF(Grade)-60-(Conn.)-(Features)	1,875	24 - 3" NPTM						49.00	1245	16.25	413	120	54.4	E (Grade)-PV	3				
HF(Grade)-64-(Conn.)-(Features)	2,500	4F - 4" ANSI Flange						52.25	1327	20.00	508	179	81.2	E (Grade)-PV	4				
HF(Grade)-68-(Conn.)-(Features)	3,125							52.25	1327	20.00	508	182	82.6	E (Grade)-PV	5				
HF(Grade)-72-(Conn.)-(Features)	5,000							6F - 6" ANSI Flange	54.63	1387	24.00	610	271	123	E (Grade)-PV	8			
HF(Grade)-76-(Conn.)-(Features)	6,875	6F - 6" ANSI Flange						62.56	1589	28.00	711	518	235	E (Grade)-PV	11				
HF(Grade)-80-(Conn.)-(Features)	8,750							62.56	1589	28.00	711	527	239	E (Grade)-PV	14				
HF(Grade)-84-(Conn.)-(Features)	11,875							8F - 8" ANSI Flange	69.13	1726	33.00	838	709	322	E (Grade)-PV	19			
HF(Grade)-88-(Conn.)-(Features)	16,250	8F - 8" ANSI Flange						67.94	1726	39.00	991	918	416	E (Grade)-PV	26				
HF(Grade)-92-(Conn.)-(Features)	21,250	10F - 10" ANSI Flange						70.94	1802	45.88	1165	1412	640	E (Grade)-PV	34				

### Filter Grades

- 11 - Mechanical Separator (bulk liquid)
- 9 - Separator/Filter (3 micron and bulk liquid)
- 7 - Air Line Filter (1 micron)
- 6 - Dry Desiccant Afterfilter (1 micron)
- 5 - High Efficiency Oil Removal Filter (0.008 ppm)
- 3 - Maximum Efficiency Oil Removal Filter (0.0008 ppm)
- 1 - Oil Vapor Removal Filter (activated carbon)

### Features:

- D - Internal Automatic Drain Mechanism
- G - Differential Pressure Gauge Indicator
- L - Liquid Level Indicator
- M - Filter Monitor
- P - Differential Pressure Slide Indicator
- S - Corrosion Proof Stainless Steel Cores
- X - External Drain Adapter

<sup>(1)</sup> Drain plugs standard. Externally mounted automatic drains are available.

<sup>(2)</sup> Time-based Filter Monitor recommended

# Filter Monitor



## Serious Savings with Filter Monitor

Titans of industry know how costly compressed air generation can be. Companies that are serious about reducing costs generally consult professional compressed air system auditors to analyze their air generation systems and plant air demands so they can strategize on areas to eliminate waste and improve efficiencies. It is no wonder that many Filters are ordered and installed with an optional Filter Monitor.

## Annual Energy Saving Potential

Flow SCFM	System Pressure Reductions				
	2 psig	4 psig	6 psig	8 psig	10 psig
100	\$143.77	\$ 287.54	\$ 431.31	\$ 575.08	\$ 718.85
250	359.42	718.85	1,078.27	1,437.69	1,797.11
500	718.85	1,437.69	2,156.54	2,875.38	3,594.23
1,000	1,437.69	2,875.38	4,313.07	5,750.76	7,188.46
2,000	2,875.38	5,750.76	8,626.15	11,501.53	14,376.91
5,000	7,188.46	14,376.91	21,565.37	28,753.82	35,942.28
10,000	14,376.91	28,753.82	43,130.74	57,507.65	71,884.56

\* Assumes 5 scfm/HP, \$0.10 per kWh, 8,760 hours of operation per year

Filter Monitor's accuracy lets you manage element condition to reduce costly system pressure.  
Example: 500 scfm air system - change filter element at 2 psig vs. 10 psig to add \$2,875.38 to your bottom line.

## Take Control

Filter Monitor uses advanced microprocessor technology to help you take control with 3 complementary modes of operation – as standard.

- Time Monitoring Mode – provides notification when it is time to change the filter element per your selection from 1-15 months.
- Differential Pressure Mode - select the exact pressure differential you will tolerate to initiate the warning to minimize the cost of pressure drop.
- Filter Performance Mode – Filter Monitor automatically analyzes your systems flow dynamics 1,800 times per hour to chart its unique operating characteristics. It references the parameters you selected and continually plots your system's profile to forecast the days left until it will cost more to operate the dirty element than to replace it. A warning is triggered 60 days before change-out is recommended and the day's countdown until the filter element is changed.

**SPX HANKISON**

**SPX Air Treatment**  
1000 Philadelphia Street  
Canonsburg, PA 15317-1700 U.S.A.  
Phone: 724-745-1555 • Fax: 724-745-6040  
Email: [hankison.inquiry@airtreatment.spx.com](mailto:hankison.inquiry@airtreatment.spx.com)  
[www.hankisonintl.com](http://www.hankisonintl.com)

©2005 SPX Air Treatment. All rights reserved. Inv# DBR-500-NA-6

Improvements and research are continuous at SPX Hankison  
Specifications may change without notice.

